



WANSEMI
万芯半导体

WX080N07KF

Enhancement Mode N-Channel Power MOSFET

TO-263/NMOS/68V/ $\pm 20V$ /2.9V/80A/6.3m Ω

Rev0.5

68V, 6.3mΩ, 80A, N-Channel Enhancement MOSFET


1.Features

- ◆ 68V MOSFET technology
- ◆ Low on-state resistance
- ◆ Fast switching
- ◆ $V_{GS} \pm 20V$
- ◆ 100% RG Tested
- ◆ 100% UIS Tested

V_{DS}	$R_{DS(on)}$ Typ.	I_D Max.
68V	6.3mΩ @ 10V	80A

2.Applications

- ◆ Power Switching Application
- ◆ Load Switching



Schematic Diagram

3.Package Marking and Ordering Information

Part no.	Marking	Package	PCS/Reel	PCS/CTN.
WX080N07KF	080N07	TO-263	800	4,800

4.Absolute Max Ratings at $T_a=25^{\circ}C$ (Note1)

Parameter	Symbol	Maximum	Units
Drain to Source Voltage	V_{DSS}	68	V
Gate to Source Voltage	V_{GSS}	± 20	V
Drain Current (DC)	I_D	80	A
Drain Current (Pulse), $PW \leq 300\mu s$	I_{DP}	320	A
Total Dissipation	P_D	103	W
Avalanche Energy, Single Pulsed	E_{AS}	370.56	mJ
Junction Temperature	T_j	175	$^{\circ}C$
Storage Temperature	T_{stg}	-55 to +175	$^{\circ}C$

Note 1: Stresses exceeding those listed in the Maximum Ratings table may damage the device. If any of these limits are exceeded, device functionality should not be assumed, damage may occur and reliability may be affected.

5. Thermal Resistance Ratings

Parameter	Symbol	Value	Unit
Junction to Case	$R_{\theta JC}$	1.46	$^{\circ}\text{C/W}$


Note 2: When mounted on 1 inch square copper board $t \leq 10\text{sec}$ The value in any given application depends on the user's specific board design.

6. Electrical Characteristics at $T_a=25^{\circ}\text{C}$ (Note 3)


Parameter	Symbol	Test Conditions	Min.	Typ.	Max.	Units
Drain to Source Breakdown Voltage	$V_{(BR)DSS}$	$I_D = 250\mu\text{A}$, $V_{GS} = 0\text{V}$	68	-	-	V
Zero-Gate Voltage Drain Current	I_{DSS}	$V_{DS} = 68\text{V}$, $V_{GS} = 0\text{V}$	-	-	1	μA
Gate to Source Leakage Current	I_{GSS}	$V_{GS} = \pm 20\text{V}$, $V_{SS} = 0\text{V}$	-	-	± 100	nA
Gate Threshold Voltage	$V_{GS(th)}$	$V_{DS}=V_{GS}$, $I_{DS}=250\mu\text{A}$	2.4	2.9	3.7	V
Static Drain to Source On-State Resistance	$R_{DS(on)}$	$I_D = 30\text{A}$, $V_{GS} = 10\text{V}$	-	6.3	7.6	m Ω
Input Capacitance	C_{iss}	$V_{GS}=0\text{V}$, $V_{DS}=30\text{V}$, Frequency=1.0MHz	-	4387	-	nF
Output Capacitance	C_{oss}		-	238	-	pF
Reverse Transfer Capacitance	C_{rss}		-	44	-	pF
Turn-ON Delay Time	$t_{d(on)}$		-	15	-	ns
Rise Time	t_r	$V_{DS} = 30\text{V}$, $I_D = 30\text{A}$, $V_{GS} = 10\text{V}$, $R_G = 3\Omega$	-	90	-	ns
Turn-OFF Delay Time	$t_{d(off)}$		-	45	-	ns
Fall Time	t_f		-	30	-	ns
Total Gate Charge	Q_g	$V_{DS} = 30\text{V}$, $V_{GS} = 10\text{V}$, $I_D = 30\text{A}$	-	35	-	nC
	Q_{gs}		-	10	-	nC
	Q_{gd}		-	9	-	nC
Diode Forward Voltage	V_{FSD}	$I_S = 30\text{A}$, $V_{GS} = 0$	0.5	-	1.2	V

Note 3: Product parametric performance is indicated in the Electrical Characteristics for the listed test conditions, unless otherwise noted. Product performance may not be indicated by the Electrical Characteristics if operated under different conditions.


7. Typical electrical and thermal characteristics




Output Characteristics




Typical Transfer Characteristics




On-resistance vs. Drain Current




Body Diode Characteristics




Gate Charge Characteristics




Capacitance Characteristics




Normalized Breakdown Voltage vs.
Junction Temperature




Normalized on Resistance vs.
Junction Temperature



Maximum Safe Operating Area




Maximum Continuous Drain Current vs.
Case Temperature



Maximum Effective Transient
Thermal Impedance, Junction-to-Case

8.Package Dimensions



9. Important Notice

WAN SEMICONDUCTOR (NINGBO) CO.,LTD reserves the right to make corrections, enhancements, improvements and other changes to its semiconductor products and services and to discontinue any product or service. Buyers should obtain the latest relevant information before placing orders and should verify that such information is current and complete. All semiconductor products (also referred to herein as “components”) are sold subject to WANSEMI’s terms and conditions of sale supplied at the time of order acknowledgment.

WANSEMI warrants performance of its components to the specifications applicable at the time of sale, in accordance with the warranty in WANSEMI’s terms and conditions of sale of semiconductor products. Testing and other quality control techniques are used to the extent WANSEMI deems necessary to support this warranty. Except where mandated by applicable law, testing of all parameters of each component is not necessarily performed.

WANSEMI assumes no liability for applications assistance or the design of Buyers’ products. Buyers are responsible for their products and applications using WANSEMI components. To minimize the risks associated with Buyers’ products and applications, Buyers should provide adequate design and operating safeguards.

No WANSEMI components are authorized for use in FDA Class III (or similar life-critical medical equipment) unless authorized officers of the parties have executed a special agreement specifically governing such use.

Unless WANSEMI has specifically designated certain components which meet ISO/TS16949 requirements, mainly for automotive use, WANSEMI will not be responsible for any failure of such components to meet such requirements.